# **CHRYSO®Metalis**

For decorative finishes

Chryso

Concrete

7/10/2024

### DESCRIPTION

CHRYSO®Metalis is real metal powder that can be applied on CHRYSO®Metalis is available in 6 metal types. various types of support. CHRYSO®Metalis is applied as a thin coating, +/- 0.5mm, to embellish existing support.

#### **BENEFITS**

- Unique look
- Easy to apply
- Modern, Highly appreciated by architects
- Multiple finishing effects

### PACKAGING

1 kg bucket

**FIELDS OF APPLICATION** 

CHRYSO<sup>®</sup>Metalis is applicable on furniture.

CHRYSO®Metalis is applicable in overlay for all supports.

CHRYSO®Metalis is not appropriate for humid environments

(bathroom, shower, sink unit), worktop, flooring, exterior surfaces.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chrysogulf.com CHRYSO Gulf LLC, P.O. Box 22849 - Doha - QATAR Tél::(+974) 4450 0840 Fax:(+974) 44500830 e-mail:admin@chrysogulf.com





# **CHRYSO®Metalis**

For decorative finishes

# **INDICATIVE INFORMATION**

Product Nature	powder
Color	According to colour chart
Water solubility	Soluble with water

## **METHOD OF USE**

CHRYSO® Metalis system is composed of a main Metalis coat and a sealer or wax:

- 1. Main finishing coat: Metalis mixed with water
- 2. Sealer or wax: depending on CHRYSO® Metalis reference
- CHRYSO<sup>®</sup>Metalis will be mixed with water before application.
- CHRYSO<sup>®</sup>Metalis main coat will dry in a few hours, depending . on the ambient temperature.
- Application should be done according to CHRYSO recommendation and may require training or support to the application team.

#### **Consumption**:

0.5 to 2 kg per m<sup>2</sup>

### PRECAUTIONS

- The application of CHRYSO®Metalis requires tools and the proper training to achieve the best result. Please contact your local CHRYSO representative for tools and training.
- Application timing may vary depending on the local conditions, especially temperature and humidity.

# **SAFETY**

Prior to any use, please read carefully the Material Safety Data Sheets.

Chryso Decorative

Concrete

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chrysogulf.com CHRYSO Gulf LLC, P.O. Box 22849 - Doha - QATAR Tél.:(+974) 4450 0840 Fax:(+974) 44500830 e-mail:admin@chrysogulf.com

