

CHRYSO®Dem DMN CQ 5

Delayed mould release agent
Mineral



DESCRIPTION

CHRYSO®Dem DMN CQ 5 is a delayed mould release agent allowing an easy demoulding of concrete after setting. The entrapped air escapes easily and has a favourable influence on the appearance of the released concrete. Facings are smooth, bright and free of veining.

BENEFITS

CHRYSO®Dem DMN CQ 5 forms on the surface of the shutter a non-adhering film that favors the separation of the concrete and the mould after the setting of concrete. It is particularly suited to metallic surfaces and especially shutters and vertical formwork.

PACKAGING

- 210 L drum
- IBC 1000L

FIELDS OF APPLICATION

- Steam-cured or non steam-cured concrete
- Aesthetic concrete
- Architectural concrete
- Metallic formworks
- Plastic formworks
- Plywood formworks
- White or plain concretes
- etc

CHRYSO® Dem DMN CQ 5

Delayed mould release agent
Mineral

INDICATIVE INFORMATION

Product Nature	liquid
Color	Brown
Lifetime	12 months
Specific gravity	0,820 ± 0,020
Flash Point	>= 65 °C

METHOD OF USE

- This product must be applied by spraying, with a roll or a paint brush, in a regular film, without any gaps or overload.
- Using the adequate spraying equipment will improve the product's performances.

Consumption:

- Steel mould: 40 m²/l.
- Wooden mould: 25 m²/l.

The consumption of this product depends on the type of support and the application process.

PRECAUTIONS

- Protect from frost.
- Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.
- Store in a dry place, away from light and any source of heat.

Compatibility:

For special support (synthetic or PU type) or applications with white cement, it is advisable to run a compatibility test before any particular use.

SAFETY

Prior to any use, please read carefully the Material Safety Data Sheets.