

# Jontec Eternum Wax

Wax

### DESCRIPTION

**Jontec Eternum Wax** is a high-gloss, slip-resistant floor emulsion for most types of smooth and water resistant, hard floors. Its technology gives superior traffic resistance against scuffs and dirt. It ensures reduced maintenance costs to improve productivity. Easy to apply, it will be ideal in all prestige and heavy traffic areas where ordinary emulsions require a high level of maintenance.

**Jontec Eternum Wax** is suitable to protect Micro-Topping surfaces, especially for flooring applications. **Jontec Eternum Wax** is a ready-to-use product.

### BENEFITS

- High-gloss, protective layer
- Hard, durable and wear resistant protection
- Easy to apply, short drying time
- Slip resistant according to international standards (ASTM D-2047)
- Easy to repair

### PACKAGING

- 5L Container

### FIELDS OF APPLICATION

- Most floor types such as vinyl, synthetic, linoleum, stone, sealed wood and cork floors, including cementitious Micro-Topping
- Residential, commercial areas
- Pedestrian heavy traffic area
- Interior areas

## Jontec Eternum Wax

Wax

### INDICATIVE INFORMATION

Product Nature	liquid
Color	Milky white
Lifetime	12 months
Water solubility	Soluble
Specific gravity	1,040 ± 0,020
pH	8,50 ± 2,00

### METHOD OF USE

- Treat only stripped and thoroughly rinsed and completely dry floors.
- Treat porous and damaged floors with one of CHRYSO floor sealers prior to application.
- Sparingly pour **Jontec Eternum Wax** onto the floor and evenly spread it while still wet with a polish applicator in overlapping lanes of 1 - 1.5 m.
- Allow to dry completely (20 - 30 minutes) before applying additional coats in similar manner. Apply two coats to non-porous, smooth floors. Three coats are usually sufficient for porous floors.

#### Linoleum:

- After the first coat has dried, smooth the linoleum floor with a single disc machine equipped with a blue pad, then damp mop and allow to dry completely before applying additional coats.

#### Top stripping and recoating:

- Use a floor stripper to remove one coat of polish and pick up soiled solution with a scrubber drier or wet vacuum cleaner. Allow to dry completely and apply additional coat(s).

#### **Consumption :**

- approximately 20 to 40 ml/m<sup>2</sup>
- Typical application ratio for a 5 liters can is 70 m<sup>3</sup> applied in 3 layers.

### PRECAUTIONS

- **Jontec Eternum Wax** is a ready-to-use product and should be used undiluted.
- Store in original closed containers at temperatures above 6°C.
- Protect from frost and direct sun exposure'
- Do not dilute or mix with other substances.
- Do not use on structured plastic (cushioned vinyl) and unsealed wood or cork
- Seek advice for use on profiled/studded rubber floors.
- Do not use outdoors or in wet zones.
- Only for professional users/specialists.

### SAFETY

Prior to any use, please read carefully the Material Safety Data Sheets.