

CHRYSO®MT - Finishing Powder

Decorative millimetric renovating overlay



DESCRIPTION

CHRYSO®MT - Finishing Powder is a powder based on hydraulic binders. Once mixed with CHRYSO®MT- BC Binder, it composes the final coat of the **CHRYSO®Proskin** system for a concrete mineral aspect overlay.



BENEFITS

- High bonding properties
- High abrasion resistance

PACKAGING

- 20 kg bag

FIELDS OF APPLICATION

- Interiors floors and walls
- Residential and commercial areas
- Wood elements (various objects, furniture)
- Kitchen furniture (workplan, ...)

CHRYSO®MT - Finishing Powder

Decorative millimetric renovating overlay

INDICATIVE INFORMATION

Product Nature	powder
Color	White
Lifetime	12 months

METHOD OF USE

CHRYSO®MT - Finishing Powder is a constituent of **CHRYSO®Proskin** micro topping system.

It composes the final coat of the system. It is recommended to apply it in two coats to obtain a uniform surface, with a « close » and smoothly troweled aspect (non-grainy aspect).

- 1 liter of CHRYSO®MT – BC Binder for 1.0 kg of **CHRYSO®MT - Finishing Powder**.
- In case of manual application: 1 liter of CHRYSO®MT – BC Binder for 2 kg of **CHRYSO®MT - Finishing Powder**.
- Pigments are dosed according to the targeted color following CHRYSO recommendations.

Equipment :

There are several techniques to apply the coat based on **CHRYSO®MT - Finishing Powder**:

1. Manual trowel (iron, stainless steel or chrome according to the targeted aspect)
2. Rubber Magic Trowel: this flexible plaster trowel allows to minimize burning marks, however the consumption is increased.

CHRYSO®MT - Finishing Powder should be used with **CHRYSO** products to achieve a full and reliable process. Other information can be found in the tutorials and references. Because local job conditions vary, please contact your local Chryso sales representative for further assistance.

Consumption :

- Follow **CHRYSO®Proskin** application methodology.

PRECAUTIONS

- Shelf life information only applies to product stored in genuine packaging.
- Store in a well ventilated location.

The consumption can vary slightly according to the type of application tool.

SAFETY

Prior to any use, please read carefully the Material Safety Data Sheets.